

## **PRODUCT DESCRIPTION**

**LEAD EXA 4T Super** is a synthetic technology 4-Stroke lubricant. Excellent shear resistance protecting engine and gearbox. Smooth shifting. Meets JASO MA2 specifications for optimal wet clutch performance.

## **APPLICATION**

Primarily intended for general use in all types of four-stroke motorcycles and engines, especially Hero, Yamaha and Honda with <150 cc engines. Suitable for catalytic converters.

## **PROPERTIES**

- Good wear protection
- Thermal and oxidation stability
- Helps keep engines clean for smoother operation
- Helps extend engine life

## **PERFORMANCE LEVELS**

Meets and exceeds:

API SN/ SL / SJ / SH / SG; JASO MA / MA2

## **TYPICAL PROPERTIES**

PARAMETERS	TEST METHOD	UNIT	LEAD EXA 4T SUPER	
Viscosity Grade			10W30	10W40
Density @ 15°C	ASTM D1298	kg/l	0.870	0.871
Viscosity @ 100°C	ASTM D445	cSt	11.50	13.82
Viscosity @ 40°C	ASTM D445	cSt	76	89.9
Viscosity Index (min)	ASTM D2270	-	155	155
Pour Point	ASTM D97	°C	-33	-33
Flash Point	ASTM D92	°C	226	226
Total Base Number (TBN)	ASTM D2896	KOH/g	7.5	7.5

The values shown above are typical values at the date of publication. Kingdom Petroleum reserves the right to change these typical values without prior notice

## **HEALTH & SAFETY, ENVIRONMENT:**

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.leadpetroleum.com](http://www.leadpetroleum.com).