

## PRODUCT DESCRIPTION

LEAD TERA 4T Eco SAE 20W40 / 20W50 is a mineral motorcycle oil designed primarily for on-road, four-cycle bikes. It also may be used in other types of on and off-road four-cycle motorcycles. Meets JASO MA1 specifications for optimal wet clutch performance. Suitable for old motorcycles.

## PERFORMANCE LEVELS

Meets and exceeds:

- API SG; JASO MA / MA1

## TYPICAL PROPERTIES

| PARAMETERS                     | TEST METHOD | UNIT  | LEAD TERA 4T ECO |       |
|--------------------------------|-------------|-------|------------------|-------|
| Viscosity Grade                |             |       | 20W40            | 20W50 |
| Density @ 15°C, kg/l           | ASTM D1298  | kg/l  | 0.880            | 0.880 |
| Viscosity @ 100°C, cSt         | ASTM D445   | cSt   | 14.0             | 18.5  |
| Viscosity @ 40°C, cSt          | ASTM D445   | cSt   | 100              | 160   |
| Viscosity Index (min)          | ASTM D2270  | -     | 142              | 126   |
| Pour Point, °C                 | ASTM D97    | °C    | -30              | -25   |
| Flash Point, °C                | ASTM D92    | °C    | 230              | 230   |
| Total Base Number (TBN), KOH/g | ASTM D2896  | KOH/g | 7.0              | 7.0   |

The values shown above are typical values at the date of publication. Lead Petroleum reserves the right to change these typical values without prior notice

## HEALTH & SAFETY, ENVIRONMENT:

Prolonged and repeated contact with oil may cause skin disorders. Avoid contact. Wash immediately with soap and water. Do not discharge used oil in to drains or the environment. Dispose to an authorized used oil collection point. For further Information on Safety Guidelines please refer to MSDS available on our website [www.leadpetroleum.com](http://www.leadpetroleum.com).